

Wash Care Oil

Technical Data Sheet

March 2020

Page 1/1



- » *dirt resistant, water-repellent, resistant to treading*
- » *Saliva and perspiration*
- » *breathable and healthy.*
- » *easy to clean surfaces*
- » *satin matt surface*
- » *suitable for hot water underfloor heating*

Product characteristics:

SAICOS Wash Care Oil, the liquid wood care product made from natural ingredients. For the maintenance of heavily used wood and cork surfaces.

Anti-Slip R9.

Colour:

8145 Clourless

Fields of application:

Especially for oiled and waxed wood surfaces. Also well suited for furniture and other interior wood.

Application:

Clean the surfaces to be treated with *Ecoline Magic Cleaner*.

Acclimatize containers to room temperature before use. Shake well before use. Pour one cap full (per 1 m²) on the clean floor, rub evenly with the *SAICOS Telescope-Maintenance Cloth* and let dry.

Removal of stubborn stains:

pour small quantity of *SAICOS Wash Care Oil* on the floor and rub stain with a rag. Never use steel wool, filament mop (microfibre) or abrasive cleaners!

Drying time:

Approx. 3 hours. Ensure that windows are open during and after application. Oxidative drying – ensure good ventilation. Remove any surplus with an absorbent cloth or machine with a white pad.

Number of treatment: annually (or as required)

Best processing temperature: Between 8 °C and 35 °C.

Coverage per liter: 1 Liter = approx. 100 m² / 1 cap for approx. 1 m²

Storage: In closed container unlimited. The liquid product is not susceptible to frost - to restore spreadability after frost, store at room temperature for several hours and shake well.

Physical characteristics:

Density: 0.81 - 0.85 g/cm³

Odour: weak / mild (after natural vegetable oils and waxes), odorless after drying.

Flashpoint: 28 °C

Safety Instructions – First Aid:

Keep out of the reach of children. Do not fill into containers normally used for food and drink. Flammable liquid and vapour. No smoking. Normally inflammable after drying. Wash out any product-soaked rags immediately or store in an airtight container (danger of combustion). May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. Ground and bond container and receiving equipment. Use explosion-proof electrical equipment. Use non-sparking tools. Avoid breathing vapours. Take action to prevent static discharges. Use only outdoors or in well ventilated areas. Avoid release to the environment. Wear protective gloves and eye/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower). IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER / doctor if you feel unwell. In case of fire: Use extinguishing powder or sand to extinguish. Store container tightly closed in a well-ventilated place. Keep cool. Keep locked up. Dispose of contents/container to industrial incineration plant.

Contains: hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes <2 % aromatics.

UN1263

Our application advice is provided to the best of our knowledge and based on experiments, however, applies only as a non-binding recommendation and does not exempt you from testing the products supplied by us as to their suitability for the intended purpose. Since the application and processing of the products is beyond our control, the responsibility rests solely with the user. With publishing a new technical data sheet the previous loses its validity.

SAICOS COLOUR GmbH

Carl-Zeiss-Str. 3

D-48336 Sassenberg

☎ +49 2583 3037-0

☎ +49 2583 3037-10

info@saicos.de

www.saicos.de